

# Sepaks ST 110 Plus

Products > Construction Chemicals > Formwork Oils



A high performance concrete mold release oil formulated with highly refined mineral oils. It provides easy separation of molds and gives excellent surface properties to concrete. It has superior lubricity thanks to the fatty acids it contains. It also increases mold life and increases its efficiency.

## ■ Fields of Application

- Steel Molds – Tunnel Molds

## ■ Advantages

- Provides easy separation of mold and concrete
- Extends the life of molds
- Prevents the formation of concrete dust
- Provides flat and smooth surface properties
- Protects molds against rust
- Resistant to curing temperatures

---

## ■ Application

Sepaks ST 110 Plus is applied by brush/roll or automatic/manual spraying. Depending on the type of formwork, 1 liter of product covers a surface of 20 m<sup>2</sup> by roller and approximately 45 m<sup>2</sup> by spraying. Make sure that the formwork is clean before application, concrete and rust residues should be cleaned beforehand.

## ■ Human Health and Occupational Safety

As long as occupational safety and personal hygiene rules are applied, it does not pose a problem in terms of human health and occupational safety. For more detailed information, Material Safety Sheets (MSDS) should be consulted.

## ■ Packaging and Storage

The product should be kept sealed in its original packaging in stock. Storage period is 36 months. Available in 30 liter drums, 200 liter barrels, 1000 liter IBCs.



## TECHNICAL DATAS

SEPAKS ST 110 PLUS	TEST METHOD	102
APPEARANCE	IMAGE	YELLOW, CLEAR LIQUID
DENSITY @15°C, g/cm <sup>3</sup>	ASTM D 4052	0,87
KINEMATIC Viscosity @ 40°C, cSt	ASTM D 445	15-17
FLASH POINT (COC) , °C	ASTM D 92	MİN. 180
YIELD POINT , °C	ASTM D 97	MAKS. 10